

Aqualift F XL, 200 L lift. stat. Duo, SPF 4500-S1



Article information

Item no.: 11120
 GTIN: 4026092057872
 Price group: 50

Advantages

- Different performance classes available
- Pressure sensor for reliable pneumatic level measurement
- Maximum operating reliability due to intelligent control unit (Duo)

Description

The lifting station for faecal and faecal-free wastewater is equipped with one or two submersible pumps and a backflow preventer. The collection tank made of permanently resistant polymer (PE) offers universal connection options and has a screwed access cover.

Variant

| | |
|---------------------------|------------------------|
| Type of system: | duo pump |
| Shut-off valve: | without shut-off valve |
| Backflow preventer: | integrated |
| Pressure pipe connection: | vertical |

General characteristics

| | |
|-------------------------|----------------------------|
| Colour: | black |
| Standard: | EN 12050-1 |
| Type of wastewater: | with sewage |
| Installation situation: | free-standing installation |
| System type: | Duo |
| ATEX: | no |

Dimensions

| | |
|----------------------|--------|
| Net weight: | 195 kg |
| Gross weight: | 215 kg |
| Packaging dimension: | length |
| Packaging dimension: | width |
| Packaging dimension: | height |

Tank/drain body

| | |
|--------------|-------|
| Tank volume: | 200 l |
|--------------|-------|

Pumping device
Pump: SPF 4500
Number of pumps: 2
Operating mode: S1
Type of fuse required (electrical protection): 3 x C 25 A
Impeller type: Multi-vane impeller
Free passage: 40 mm
Length of mains cable for pump: 5 m

Control
Control unit: Comfort
Level measurement instrument: Immersion pipe
Type of level measurement: pneumatic
Mains frequency: 50 Hz
Operating voltage: 400 V
Type of fuse required (electrical protection): 3 x C 25 A