


Submersible pump Aquadive GTF1000 resistant, without float switch, 10 m



Article information

Item no.: 28760C
GTIN: 4026092093764
Price group: 20

Advantages

- Multi-vane vortex impeller for maximum reliability
- Longitudinally watertight potted connection cable
- Integrated shallow extraction

Description

Submersible pump for faecal-free wastewater

Variant

Resistant:

Resistant to saline media, wastewater from water softening systems and wastewater containing condensate from heating systems without float switch

Pump control:

General characteristics

Standard:

EN 12050-2

Type of wastewater:

without sewage

ATEX:

no

Dimensions

Net weight:

9,7 kg

Gross weight:

10 kg

Length:

195 mm

Width:

195 mm

Height:

290 mm

Packaging dimension:

length

Packaging dimension:	width
Packaging dimension:	height
Wastewater contents	
Pressure pipe connection:	R 1 ¼"
Pumping device	
Pump:	GTF 1000 resistant
Connection type:	coded plug
Rated current:	5,6 A
Protection class:	I
Insulation class:	F
Protection class (pump):	IP 68 (3m)
Max. temperature (permanent) of conveyed material:	40 °C
Hot water resistance for a short time (2 min):	80 °C
Max. pumping height:	10 m
Speed:	2700 U/min
Power P1:	1,3 kW
Power P2:	0,75 kW
Operating mode:	S1
Type of fuse required (electrical protection):	C 16 A
Type of pump connection cable:	H07RN-F 3G 1.5 mm ²
Impeller type:	Multi-vane impeller
Free passage:	10 mm
Length of mains cable for pump:	10 m
Control	
Mains frequency:	50 Hz
Operating voltage:	230 V
Connection type:	coded plug
Type of fuse required (electrical protection):	C 16 A