

Basement drain DN 100, Black grating, Class K 3



Article information

Item no.: 29111 GTIN: 4026092007846 Price group: 10

Advantages

- Integrated odour trap
- Including sludge bucket

Description

The basement drain made of polymer for floor slab installation is equipped with an odour trap and a sludge bucket. The upper section with slotted grating is vertically adjustable.

Variant Contents of sludge trap: Position of lateral connection: Sealing water height: Discharge rate (l/s) with 20mm threshold:	yes Type II 60 mm 1,8
General characteristics Standard:	EN 1253-1
Nominal size (DN):	100
Outer diameter (OD):	110 mm
Odour trap:	included
Dimensions	
Vertical adjustment:	30 - 90 mm
Net weight:	2,55 kg
Gross weight:	2,88 kg
Cutout dimension, width:	320 mm
Cutout dimension, length:	400 mm
Installation depth:	216 - 276 mm
Type of height adjustability:	vertically adjustable upper section
Length:	380 mm
Width:	290 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height
Tank/drain body	
Inlet nominal size (DN):	70 mm

IK KESSEL

Number of inlets: Material of drain body: Socket version:

Coverage features Type of cover: Cover material: Colour of cover: Width of cover: Length of cover: Frame material: Locking: Load class: Rim width: Rim length: Upper section material: Contents of sludge trap: 2 PP lateral

Slotted cover Polymer black 188 mm 188 mm Polymer placed K 3 (EN 1253-1) 200 mm 200 mm Polymer yes