

Practicus basement drain DN 100, Black grating, Horizontal outlet



Article information

Item no.: 34101
 GTIN: 4026092007884
 Price group: 10

Advantages

- Vertically adjustable upper section
- Suitable for floor slab installation

Description

The Practicus basement drain is made of polymer and is suitable for floor slab installation. The upper section with slotted grating is vertically adjustable.

Variant

Contents of sludge trap:	yes
Discharge rate (l/s) with 10 mm threshold:	1,1
Discharge rate (l/s) with 20 mm threshold:	1,8

General characteristics

Standard:	EN 1253-2
Nominal size (DN):	100
Outer diameter (OD):	110 mm
Odour trap:	no

Dimensions

Net weight:	1,39 kg
Gross weight:	1,61 kg
Cutout dimension, width:	180 mm
Cutout dimension, length:	220 mm
Installation depth:	152 - 208 mm
Type of height adjustability:	vertically adjustable upper section
Length:	188 mm
Width:	150 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height

Tank/drain body

Number of outlets:	1
Material of drain body:	Polymer
Socket version:	lateral

Coverage features

Type of cover:	Slotted cover
Cover material:	Polymer
Colour of cover:	black
Width of cover:	138 mm
Length of cover:	138 mm
Surface:	Polished SST
Frame material:	Polymer
Locking:	placed
Load class:	K 3 (EN 1253-1)
Shape of upper section:	square
Upper section material:	Polymer
Contents of sludge trap:	yes