

## Practicus basement drain DN 100, Black grating, Vertical outlet



### Article information

Item no.: 34102  
 GTIN: 4026092047705  
 Price group: 10

### Advantages

- Vertically adjustable upper section
- Suitable for floor slab installation

### Description

The Practicus basement drain is made of polymer and is suitable for floor slab installation. The upper section with slotted grating is vertically adjustable.

#### Variant

Contents of sludge trap:	yes
Discharge rate (l/s) with 10 mm threshold:	1,1
Discharge rate (l/s) with 20 mm threshold:	1,8

#### General characteristics

Standard:	EN 1253-2
Nominal size (DN):	100
Outer diameter (OD):	110 mm
Odour trap:	no

#### Dimensions

Net weight:	1,33 kg
Gross weight:	1,55 kg
Cutout dimension, width:	180 mm
Cutout dimension, length:	180 mm
Installation depth:	221 - 277 mm
Type of height adjustability:	vertically adjustable upper section
Length:	150 mm
Width:	150 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height

#### Tank/drain body

Number of outlets:	1
Material of drain body:	Polymer
Socket version:	vertical

## Coverage features

Type of cover:	Slotted cover
Cover material:	Polymer
Colour of cover:	black
Width of cover:	138 mm
Length of cover:	138 mm
Frame material:	Polymer
Locking:	placed
Load class:	K 3 (EN 1253-1)
Shape of upper section:	square
Upper section material:	Polymer
Contents of sludge trap:	yes