

Variofix Classic bathroom drain DN 50, vert., Slotted grating, K 3



Article information

Item no.: 40250.50 GTIN: 4026092028599 Price group: 10

Advantages

- Odour trap height: 50 mm
- Lip seal fixed on the drain body
- Side adjustable cover

Description

The Classic bathroom drain is suitable for indoor floor drainage. The drain made of ABS is equipped with a telescopic, height-adjustable upper section made of polymer, a removable odour trap as well as a secure, reliably installed seal. Including upper section for combined waterproofing for alternative WP layer.

Variant	
Waterproofing layer on the upper section:	Enclosed sealing collar to be glued (bd) according to DIN 18534
Water exposure class in accordance to DIN 18534-1 (up to and including):	W3-I
Sealing water height:	50 mm
Discharge rate (l/s) with 20 mm threshold:	0,8
General characteristics	
Standard:	EN 1253-1
Nominal size (DN):	50
Outer diameter (OD):	50 mm
Odour trap:	included
Dimensions	
Vertical adjustment:	45 - 110 mm
Net weight:	1,28 kg
Gross weight:	1,51 kg
Cutout dimension, width:	180 mm
Cutout dimension, length:	220 mm
Type of height adjustability:	vertically adjustable upper section
Length:	312 mm
Width:	312 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height



Tank/drain body Number of outlets: Material of drain body: Socket version:

Coverage features Type of cover: Cover material: Colour of cover: Width of cover: Length of cover: Surface: Frame material: Locking: Load class: Rim width: Rim length: Shape of upper section: Upper section material: 1 ABS vertical

Slotted cover Stainless steel 14301 silver 95 mm 95 mm Polished SST ABS placed K 3 (EN 1253-1) 132 mm 132 mm square ABS