

Variofix Classic bathroom drain DN 70, vert., Slotted grating, K 3



Article information

Item no.: 40270.50
 GTIN: 4026092029510
 Price group: 10

Advantages

- Odour trap height: 50 mm
- Lip seal fixed on the drain body
- Side adjustable cover

Description

The Classic bathroom drain is suitable for indoor floor drainage. The drain made of ABS is equipped with a telescopic, height-adjustable upper section made of polymer, a removable odour trap as well as a secure, reliably installed seal. Including upper section for combined waterproofing for alternative WP layer.

Variant

Waterproofing layer on the upper section:	Enclosed sealing collar to be glued (bd) according to DIN 18534
Water exposure class in accordance to DIN 18534-1 (up to and including):	W3-I
Sealing water height:	50 mm
Discharge rate (l/s) with 20 mm threshold:	0,8

General characteristics

Standard:	EN 1253-1
Nominal size (DN):	70
Outer diameter (OD):	75 mm
Odour trap:	included

Dimensions

Vertical adjustment:	45 - 110 mm
Net weight:	1,46 kg
Gross weight:	1,7 kg
Cutout dimension, width:	180 mm
Cutout dimension, length:	220 mm
Type of height adjustability:	vertically adjustable upper section
Length:	312 mm
Width:	312 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height

Tank/drain body	
Number of outlets:	1
Material of drain body:	ABS
Socket version:	vertical
Coverage features	
Type of cover:	Slotted cover
Cover material:	Stainless steel 14301
Colour of cover:	silver
Width of cover:	95 mm
Length of cover:	95 mm
Surface:	Polished SST
Frame material:	ABS
Locking:	placed
Load class:	K 3 (EN 1253-1)
Rim width:	132 mm
Rim length:	132 mm
Shape of upper section:	square
Upper section material:	ABS