


## Practicus floor/roof drain DN 100, horizontal, Slotted grating





## Article information

Item no.: 45110.11 GTIN: 4026092032961

Price group: 10

## **Advantages**

- Hygiene: hygienic, absolutely corrosion-free and durable material
- Sound insulation: outstanding sound insulation effect confirmed by the Fraunhofer Institute

## **Description**

The Practicus floor drain is used for point drainage and is equipped with a connection flange as well as a removable odour trap, a lip seal and a temporary protective cover. Including telescopic height-adjustable upper section made of ABS. The drain meets particular sound insulation requirements in accordance with the measurements of the Fraunhofer Institute in Stuttgart. The outlet socket is suitable for connection to SML cast iron pipes. With connection option for equipotential bonding.

Variant

System: 125

Waterproofing layer on the upper section: Connection flange Waterproofing layer on the drain body: Connection flange

Sealing water height: 50 mm Discharge rate (l/s) with 20 mm threshold: 1,6

General characteristics

Standard: EN 1253-1
Nominal size (DN): 100
Outer diameter (OD): 110 mm
Odour trap: included

**Dimensions** 

Net weight: 1,39 kg Gross weight: 1,76 kg



Cutout dimension, width: 180 mm
Cutout dimension, length: 220 mm

Type of height adjustability: vertically adjustable upper section

Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Tank/drain body

Number of outlets: 1

Connection inlet/outlet sockets: The outlet spigot is suitable for connection to SML

pipes.

Material of drain body: PP Socket version: lateral

Coverage features

Type of cover: Slotted cover

Cover material: Stainless steel 14301

Colour of cover: silver
Width of cover: 138 mm
Height of cover: 16 mm
Length of cover: 138 mm
Surface: Polished SST

Frame material: ABS
Locking: screwed
Load class: K 3 (EN 1253-1)

Grating design: Kessel
Rim width: 150 mm
Rim length: 150 mm

Upper section: vertically adjustable

Shape of upper section: square Upper section material: ABS