

Shower channel Linearis Compact L: 450 mm, DN50, enclWPM, 304SSTcov, K3



Article information

Item no.: 45600.60 GTIN: 4026092048160 Price group: 10

Advantages

- Individual design with reversible stainless steel insert
- Low installation depth
- Highest fire protection standards

Description

The Linearis Compact shower channel with welded on drain body made of ABS is suitable for indoor linear drainage. If inserted upside down, the stainless steel insert can be tiled individually. Including prepared seepage water openings and odour trap.

Variant	
System:	125
Seepage opening:	prepared
Waterproofing layer on the upper section:	Enclosed sealing collar to be glued (bd) according to
	DIN 18534
Water exposure class in accordance to DIN	W2-I
18534-1 (up to and including):	
Sealing water height:	22 mm
Discharge rate (l/s) with 10 mm threshold:	0,6
Discharge rate (l/s) with 20 mm threshold:	0,7
Discharge rate (l/s) without threshold:	0,5 mm
-	
General characteristics	
Nominal size (DN):	50
Outer diameter (OD):	50 mm
ATEX:	no
Odour trap:	included
Dimensions	
Net weight:	1,32 kg
Gross weight:	1,83 kg
Outer dimension, length:	515 mm
Installation depth:	80 - 140 mm
Width:	191 mm
Height:	80 mm
-	



Packaging dimension: Packaging dimension: Packaging dimension:

Tank/drain body Number of outlets: Material of drain body:

Coverage features Type of cover: Cover material: Colour of cover: Surface: Frame material: Load class: Grating design: Rim width: Rim length: Max. flooring height: Shape of upper section: Upper section material: length width height

1 ABS

Stainless steel cover Stainless steel 14301 silver Brushed SST Stainless steel 14301 K 3 (EN 1253-1) optionally tileable 66 mm 450 mm 15 mm square ABS