

## Replacement pump Aquadive GTF1200 with float switch, 10 m



### Article information

Item no.: 680594  
 GTIN: 4026092078808  
 Price group: 90

### Description

Replacement pump, Aquadive GTF 1200 with floater for pumping station

#### Variant

Pump control: Float switch

#### General characteristics

Cable length: 10 m  
 ATEX: no

#### Dimensions

Net weight: 11,44 kg  
 Gross weight: 11,44 kg  
 Packaging dimension: length  
 Packaging dimension: width  
 Packaging dimension: height

#### Pumping device

Pump: GTF 1200  
 Connection type: Schuko (earthed contact) 2-pin  
 Operating voltage: 230 V  
 Mains frequency: 50 Hz  
 Rated current: 6,2 A  
 Protection class: I  
 Insulation class: F  
 Cos phi - power factor: 0,98  
 Protection class (pump): IP 68  
 Max. temperature (permanent) of conveyed material: 35 °C  
 Max. pumping height: 9 m  
 Speed: 2650 U/min  
 Power P1: 1,4 kW  
 Power P2: 0,84 kW  
 Operating mode: S3 - 50 %

Type of fuse required (electrical protection):	C 16 A
Type of pump connection cable:	H07RN-F 3G 1.5 mm <sup>2</sup>
Length of mains cable for pump:	10 m
Control	
Connection type:	Schuko (earthed contact) 2-pin
Type of fuse required (electrical protection):	C 16 A