

## Replacement pump Aquadive GTF1200 without float switch, 10 m



### Article information

Item no.: 680595  
 GTIN: 4026092078815  
 Price group: 90

### Description

Replacement pump, Aquadive GTF 1200 without floater for pumping station

#### Variant

Pump control: Control unit

#### General characteristics

Cable length: 10 m  
 ATEX: no

#### Dimensions

Net weight: 11,19 kg  
 Gross weight: 11,19 kg  
 Packaging dimension: length  
 Packaging dimension: width  
 Packaging dimension: height

#### Pumping device

Pump: GTF 1200  
 Connection type: Schuko (earthed contact) 2-pin  
 Operating voltage: 230 V  
 Mains frequency: 50 Hz  
 Rated current: 6,2 A  
 Protection class: I  
 Insulation class: F  
 Cos phi - power factor: 0,98  
 Protection class (pump): IP 68  
 Temperature monitoring: integrated  
 Max. temperature (permanent) of conveyed material: 35 °C  
 Max. pumping height: 9 m  
 Speed: 2650 U/min  
 Power P1: 1,4 kW  
 Power P2: 0,84 kW

|  |  |
|--|--|
| Operating mode:                                | S1   |
| Type of fuse required (electrical protection): | Fuse protection through control unit 230 V |
| Type of pump connection cable:                 | H07RN-F 3G 1.5 mm <sup>2</sup>             |
| Length of mains cable for pump:                | 5 m  |
| Control  |  |
| Connection type:                               | Schuko (earthed contact) 2-pin             |
| Type of fuse required (electrical protection): | Fuse protection through control unit 230 V |