

## Replacement pump SPZ 1000 resistant



### Article information

Item no.: 680951  
 GTIN: 4026092093788  
 Price group: 90

### Description

Replacement pump resistant to salty media, wastewater from water softening systems and wastewater containing condensate from heating systems.

#### General characteristics

ATEX: no

#### Dimensions

Net weight: 9,67 kg  
 Gross weight: 10,37 kg  
 Packaging dimension: length  
 Packaging dimension: width  
 Packaging dimension: height

#### Pumping device

Pump: SPZ 1000  
 Connection type: coded plug  
 Operating voltage: 230 V  
 Mains frequency: 50 Hz  
 Rated current: 5,2 A  
 Protection class: I  
 Protection class (pump): IP 68 (3m/48h)  
 Max. temperature (permanent) of conveyed material: 35 °C  
 Max. pumping height: 10 m  
 Speed: 2800 U/min  
 Power P1: 1,2 kW  
 Power P2: 0,7 kW  
 Operating mode: S3 - 50 %  
 Type of fuse required (electrical protection): C 16 A  
 Type of pump connection cable: H07RN-F 3G 1.5 mm<sup>2</sup>  
 Length of mains cable for pump: 5 m

#### Control

Connection type:

coded plug

Type of fuse required (electrical protection):

C 16 A