

Replacement pump GTF 600 w. float switch, Aqualift S 100/200, 5m



Article information

Item no.: 680976
GTIN: 4026092095898
Price group: 90

Description

Replacement pump with float switch for faecal-free wastewater.

Variant

Pump control: Float switch

General characteristics

Type of wastewater: without sewage
ATEX: no

Dimensions

Net weight: 6,8 kg
Gross weight: 6,8 kg
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Pumping device

Pump: GTF 600
Connection type: Schuko (earthed contact) 2-pin
Operating voltage: 230 V
Mains frequency: 50 Hz
Rated current: 2,9 A
Protection class (pump): IP 68 (3m)
Max. temperature (permanent) of conveyed material: 40 °C
Max. pumping height: 8 m
Speed: 2750 U/min
Power P1: 0,65 kW
Power P2: 0,4 kW
Operating mode: S1
Type of fuse required (electrical protection): C 16 A

Type of pump connection cable:	H07RN-F 3G 1.5 mm ²
Impeller type:	Multi-vane impeller
Length of mains cable for pump:	5 m
Control	
Connection type:	Schuko (earthed contact) 2-pin
Type of fuse required (electrical protection):	C 16 A