

## Replacement pump GTF 1250 w. float switch, Aqualift S 100/200, 5m



### Article information

Item no.: 680978  
GTIN: 4026092095911  
Price group: 90

### Description

Replacement pump with float switch for faecal-free wastewater.

#### Variant

Pump control: Float switch

#### General characteristics

Type of wastewater: without sewage  
ATEX: no

#### Dimensions

Net weight: 10,5 kg  
Gross weight: 10,5 kg  
Packaging dimension: length  
Packaging dimension: width  
Packaging dimension: height

#### Pumping device

Pump: GTF 1250  
Connection type: Schuko (earthed contact) 2-pin  
Operating voltage: 230 V  
Mains frequency: 50 Hz  
Rated current: 5,4 A  
Protection class (pump): IP 68 (3m)  
Max. temperature (permanent) of conveyed material: 40 °C  
Max. pumping height: 11 m  
Speed: 2700 U/min  
Power P1: 1,3 kW  
Power P2: 0,8 kW  
Operating mode: S3 - 50 %  
Type of fuse required (electrical protection): C 16 A

Type of pump connection cable: H07RN-F 3G 1.5 mm<sup>2</sup>  
Impeller type: Multi-vane impeller  
Length of mains cable for pump: 5 m

Control  
Connection type: Schuko (earthed contact) 2-pin  
Type of fuse required (electrical protection): C 16 A