
# **IK** KESSEL

## Staufix clean out DN 150, Floor slab, tileable





### **Article information**

Item no.: 700150.10X GTIN: 4026092075968 Price group: 10

#### **Advantages**

- Simple conversion to Staufix type 1
- Own gradient only 8 mm
- Quick and toolless access for cleaning

### Description

The clean out for faecal and faecal-free wastewater makes easy access to wastewater pipes possible for inspection and maintenance work. Thanks to the modular KESSEL system, existing systems can easily be supplemented by up to two flaps and one emergency closure or be converted to the StaufixControl backwater valve.

General characteristics	black
Colour:	150
Nominal size (DN):	160 mm
Outer diameter (OD):	for wastewater with and without sewage
Type of wastewater:	floor slab installation
Installation situation:	Installation-ready (connection parts must be
Delivery state:	connected on site)
Dimensions Net weight: Gross weight: Groundwater resistant from lower edge of base section: Cutout dimension, width: Cutout dimension, length:	7,6 kg 10,2 kg 3 mm 750 mm 750 mm
Vertical drop between inlet and outlet:	8 mm
Installation depth:	341 - 464 mm
Type of height adjustability:	vertically adjustable upper section



Length: Width: Packaging dimension: Packaging dimension: Packaging dimension:

Coverage features Type of cover: Cover material: Width of cover: Length of cover: Locking: Load class: Tightness: Max. flooring height: 523 mm 444 mm length width height

tileable cover plate Polymer 366 mm 366 mm Lock & Lift K 3 (EN 1253-1) surface water resistant 18 mm