

Backwater valve Staufix DN 200, exposed, Type 1



Article information

Item no.: 720200
 GTIN: 4026092076118
 Price group: 10

Advantages

- Simple conversion to Staufix Type 2 or StaufixControl
- Flexible installation, various covers available for floor slab installation
- Simple, toolless maintenance and cleaning

Description

The backwater valve for wastewater without sewage is equipped with one mechanical flap which closes automatically in the event of backwater and also serves as an emergency closure to be closed by hand. Thanks to the modular KESSEL system, existing systems can easily be supplemented by a second flap or be converted to the StaufixControl backwater valve.

Variant

Emergency closure: yes
 Mechanical backwater flaps: 1

General characteristics

Colour: black
 Standard: EN 13564
 Nominal size (DN): 200
 Outer diameter (OD): 200 mm
 Note on nominal size: Hydraulics correspond to DN 150
 Type of wastewater: without sewage
 Installation situation: exposed drainage pipe
 Delivery state: installation-ready
 Backwater protection: Type 1

Dimensions

Net weight: 3,7 kg
 Gross weight: 6,3 kg
 Vertical drop between inlet and outlet: 8 mm
 Length: 586 mm
 Width: 233 mm
 Height: 306 mm
 Packaging dimension: length

Packaging dimension:
Packaging dimension:

width
height

Coverage features

Type of cover:

Lockable cover

Cover locking:

One-handed closure