


Backwater valve Staufix DN 125, Floor slab, tileable, Type 2





Article information

Item no.: 730125.10X GTIN: 4026092076446 Price group: 10

Advantages

- Optional rat protection flap for additional safety
- Flexible installation, various covers available for floor slab installation
- Alternatively available as a module set

Description

The backwater valve for wastewater without sewage is equipped with two mechanical flaps which close automatically in the event of backwater. One flap serves as an emergency closure to be closed by hand. Thanks to the modular KESSEL system, existing systems can easily be converted to the StaufixControl backwater valve.

Variant	
Stainless steel flap as rat protection:	no
Emergency closure:	yes
Mechanical backwater flaps:	2
General characteristics	
Colour:	black
Standard:	EN 13564
Nominal size (DN):	125
Outer diameter (OD):	125 mm
Type of wastewater:	without sewage
Installation situation:	floor slab installation
Delivery state:	Installation-ready (connection parts must be
	connected on site)
Backwater protection:	Туре 2
Dimensions	
Net weight:	7,8 kg



Gross weight: Groundwater resistant from lower edge of base section: Cutout dimension, width: Cutout dimension, length: Vertical drop between inlet and outlet: Installation depth: Type of height adjustability: Length: Width: Packaging dimension: Packaging dimension: Packaging dimension:

Coverage features Type of cover: Cover material: Width of cover: Length of cover: Locking: Load class: Tightness: Max. flooring height: 750 mm 750 mm 8 mm 341 - 464 mm vertically adjustable upper section 511 mm 444 mm length width height

10,4 kg

3 mm

tileable cover plate Polymer 366 mm 366 mm Lock & Lift K 3 (EN 1253-1) surface water resistant 16 mm