

Staufix FKA conversion kit DN 100-200, fr. 01/2011, 5 m cable



Article information

Item no.: 80093
 GTIN: 4026092048245
 Price group: 30

Description

The conversion kit is equipped with a motor-driven closure system, which is closed automatically in the event of backwater. A second closure system serves as an emergency closure to be closed by hand.

The station is controlled by a user-friendly control unit, which is optionally integrated in the building management system via a potential-free contact, or alarm and collective fault messages can be output via a GSM interface.

The conversion kit is used to retrofit Staufix FKA and Controlfix for the Staufix FKA backwater valve.

General characteristics

Standard:	EN 13564
Nominal size (DN):	100-200
Note on nominal size:	Hydraulics correspond to DN 150
Type of wastewater:	for wastewater with and without sewage
Installation situation:	floor slab installation
Backwater protection:	Type 3
Type de protection moteur:	IP 68 (3m/48h)
Cable length:	5 m
ATEX:	no

Dimensions

Net weight:	5,83 kg
Gross weight:	6,79 kg
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height

Control

Control unit:	Comfort
Alarm sensor:	optical probe
Level measurement instrument:	optical probe

Type of level measurement:	optical
Protection class control unit:	IP 54
Length of mains cable for control unit:	1,4 m
Potential-free contact:	optional
GSM interface:	yes
USB interface:	yes
Log book function:	yes
Multi-line display:	yes
Battery buffering:	yes
Self-diagnosis system (SDS):	yes