

## Sampling chamber LW 400, DN 100/150, class D



### Article information

Item no.: 915880D  
 GTIN: 4026092025062  
 Price group: 60

### Description

Sampling chamber LW 400 for separators, for underground installation, draining, watertight, resistant to aggressive wastewater. Minimum installation depth can be achieved by sawing to required length. Flow direction:

straight A load distribution slab must be installed on site for load class D. The reinforcement drawings are available from KESSEL.

#### General characteristics

Colour: black  
 Material: PE

#### Dimensions

Net weight: 39 kg  
 Gross weight: 45 kg  
 Vertical drop between inlet and outlet: 120 mm  
 Installation depth: 400 - 1300 mm  
 Type of height adjustability: vertically adjustable upper section  
 Packaging dimension: length  
 Packaging dimension: width  
 Packaging dimension: height

#### Tank/drain body

Distance pipe bottom inlet to tank bottom: 120 mm  
 Outlet nominal size (OD): 110 mm  
 Outlet nominal size (DN): 100 mm  
 Inlet nominal size (OD): 110 mm  
 Inlet nominal size (DN): 100 mm  
 Clear width of tank (LW): 400 mm

#### Coverage features

Type of cover: Cover plate  
 Cover material: Grey iron  
 Colour of cover: black  
 Load class: D 400 (EN 124)

Tightness:

odour-tight and surface water resistant