

## Sampling chamber DN 200, Class D



### Article information

Item no.: 915883D  
 GTIN: 4026092048573  
 Price group: 60

### Description

Sampling chamber LW 450 for separators, for underground installation, draining, watertight, resistant to aggressive wastewater. Minimum installation depth can be achieved by sawing to required length. Flow direction:

straight A load distribution slab must be installed on site for load class D. The reinforcement drawings are available from KESSEL.

#### General characteristics

Colour: black  
 Material: PE  
 ATEX: no

#### Dimensions

Net weight: 48 kg  
 Gross weight: 54 kg  
 Vertical drop between inlet and outlet: 160 mm  
 Installation depth: 950 - 1300 mm  
 Type of height adjustability: vertically adjustable upper section  
 Length: 730 mm  
 Packaging dimension: length  
 Packaging dimension: width  
 Packaging dimension: height

#### Tank/drain body

Distance pipe bottom inlet to tank bottom: 205 mm  
 Outlet nominal size (OD): 200 mm  
 Outlet nominal size (DN): 200 mm  
 Inlet nominal size (OD): 200 mm  
 Inlet nominal size (DN): 200 mm  
 Clear width of tank (LW): 450 mm

#### Coverage features

Type of cover: Cover plate  
 Cover material: Grey iron

Colour of cover:  
Load class:  
Tightness:

black  
D 400 (EN 124)  
odour-tight and surface water resistant