

Grease separator EasyClean free NS 10, Standard



Article information

Item no.: 93010.01 GTIN: 4026092060865

Price group: 60

Advantages

- Direction of flow can be changed thanks to selfsealing interchangeable hubs (NS 2- NS 10)
- Can be retrofitted up to Auto Mix & Pump
- Low-maintenance operation

Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a tapered base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. Manual disposal is carried out with the tank open. 20 year polyethylene warranty.

Variant

Disposal variant:

Shredder-Mix-System:

no
Sludge bucket:

no
Nominal size (NS):

SonicControl:

Refill inlet in accordance with DIN 1988:

Type of disposal: manual with suction hose

Load-bearing capacity (DIN 19901): F3

General characteristics

Material: PE

Installation situation: free-standing installation

Delivery state: Installation-ready (connection parts must be

connected on site)

Dimensions

Net weight: 190 kg
Gross weight: 225 kg
Set-up area, length: 2822 mm
Set-up area, width: 951 mm
Set-up area, height: 1653 mm



Required access area, length:

Required access area, width:

951 mm

Required access area, height:

1653 mm

Packaging dimension:

Packaging dimension:

width

Packaging dimension:

height

Tank/drain body

Distance pipe bottom outlet to tank bottom:

Distance pipe bottom inlet to tank bottom:

Outlet nominal size (OD):

Outlet nominal size (DN):

Inlet nominal size (OD):

Inlet nominal size (DN):

Inlet nominal size (DN):

150 mm

Inlet nominal size (DN):

150 mm

Connection inlet/outlet sockets: PE-HD pipes in accordance with DIN 19537, HT pipes

in accordance with DIN 19560, PP or AS

Coverage features

Type of cover: Cover Cover material: Polymer Colour of cover: violet

Locking: Quick-release closure

Tightness: odour-tight

Wastewater contents

Separator contents:900 lTotal volume:1900 lContents of sludge trap:1000 lStorage quantity of grease:400 l

Control

Control unit: no