

## Coalescence separator EasyOil NS 6, class I, ø1000

### Article information

Item no.: 99706.06F  
GTIN:  
Price group: 60

### Advantages

- Permanent leak tightness up to top edge of the container
- Resistant to and suitable for up to 100 % share of biodiesel (FAME)
- Suitable for filling stations with high-performance filling pumps, E10 and biodiesel fuels

### Description

The light liquid separator is suitable for free-standing installation in frost-protected rooms and is equipped with a removable coalescence insert. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap (optional) and an automatic closure device. The odour-tight cover enables easy access for cleaning and maintenance work.

An inlet and outlet connection on site is possible with PE-HD pipes according to DIN 19537, PVC-KG pipes according to DIN 19534 and PP or AS on pipe spigots (PE) fitted at the factory. The applicable standards must be observed when selecting the appropriate seals and pipe materials.

20-year polyethylene warranty.

#### Variant

Nominal size (NS): 6,00  
Coalescence insert: yes

#### General characteristics

Standard: EN 858  
Installation situation: free-standing installation  
Separator class: I  
Range of applications for light liquids: from 0.85 to 0.95 g/cm<sup>3</sup>

#### Dimensions

Net weight: 220 kg  
Gross weight: 230 kg  
Length: 1580 mm  
Width: 1322 mm  
Height: 1615 mm

#### Tank/drain body

Distance pipe bottom outlet to tank bottom: 1155 mm  
Distance pipe bottom inlet to tank bottom: 1205 mm

Outlet nominal size (OD):	160 mm
Outlet nominal size (DN):	150 mm
Inlet nominal size (OD):	160 mm
Inlet nominal size (DN):	150 mm
Clear width of tank (LW):	1000 mm
Clear width of entry (LW):	630 mm

Coverage features	
Colour of cover:	black

Wastewater contents	
Total volume:	880 l
Contents of sludge trap:	600 l
Storage quantity of light liquid:	180 l